



111111



### **SECURING VALUABLES**

# **STORAGE SECURITY**



SHIELD products and merchandise after hours
 PROTECT equipment and unique items from theft
 SECURE valuable, confidential, and important items

## **SECURE STORAGE SHUTTERS**

#### **OPERATION**

- Spring assist manual or powered operation options available
- Control effortlessly by switch, remote, WI-FI or app
- Smooth operation with low maintenance design
- Safe, long-lasting performance with the latest in motorized technologies
- Curtain rolls into a compact coil allowing a minimal size and sleek box design

#### MATERIALS

- Minimal size, high-tech roll formed aluminum housing
- A variety of curtain styles and colors for that perfect look
- Gorgeous selection of low maintenance materials, with next
  generation powder coated finishes
- Commercial grade aluminum Environmentally friendly material with positive effects during production and long term operation
- Clamp-on or screw-on options for a clean install and lasting durability
- High strength and durability means your storage is secure and protected at all times

#### **BOTTOM BAR OPTIONS**

- 57 mm (2.25 in) or 60 mm (2.36 in) Standard Bottom Bars
- Optimum durability withstands daily wear





#### FRAME & CURTAIN COLOR OPTIONS

- Not all series are available in all colors, contact your dealer for options
- Additional charge for dark bronze, black, and custom colors





















#### SHUTTER CURTAIN STYLES AND SIZING

Pentagon TambourGuard curtain styles are finished in industry leading coatings, and provide options for visibility. Our engineered slats provide enhanced security as well as adding to the visual appeal of your facility.

					4		
400	440	450	500	530	540	560	561
Series							

SOLID CURTAIN							
	Description	400*	440*	450	500	540	560
	The solid curtain is available in 440*, 450, 500, and 560 se series provide a highly secure	ries. These aluminum with	Roll formed aluminum with ultra hard resin core	Double wall extruded aluminum	Roll formed aluminum with regular density foam filling	Roll formed aluminum with ultra hard resin core	Single wall extruded aluminum
	*Available with light slots						

PERFORATED	CURTAIN	
	Description	561
	TambourGuard is available with a perforated curtain in the 561 series. The small perforation option is designed to allow light transfer through the shutter curtain as well as optimal air flow. This perforated curtain option provides an unobstructed view through the the shutter.	Single wall extruded aluminum with small perforations

PATTERNED CURTAIN						
	Description	530				
	The patterned curtain is available using the 530 series in TambourGuard. Clear anodized connector rods are used in between each slat, adding valuable strength and visual appeal to the curtain. The curtain pattern available in TambourGuard is the clear pattern.	Clear polycarbonate /aluminum with curved design				

BOTTOM BAR SIZING	
Description	STD Bottom Bar
The TambourGuard system is compatible with the Standard Bottom Bar (two sizes) and the Heavy Duty Bottom Bar (one size). The Standard Bottom Bar is low profile and secure. The Heavy Duty Bottom Bar is extremely strong and durable.	2.25 in (57 mm) 2.36 in (60 mm)

GUIDE RAIL SIZING						
Description	53 mm	64 mm	66 mm	83 mm	83 mm - AnchorLoc	
5 sizes of guide rails available in TambourGuard. AnchorLoc secures the curtain to each guide rail.	2 in (53 mm)	2.5 in (64 mm)	2.6 in (66 mm)	3.25 in (83 mm)	3.25 in (83 mm)	

SHUTTER AND CURTAIN SIZING							
Slat Profiles	Guide Rail Sizes	Bottom Bar Sizes	Maximum Curtain Size	Maximum Curtain Area			
400, 440, 450	2 in (53 mm), 2.6 in (66 mm)	STD 2.25 in (57 mm), HD 3 in (75 mm)	Width: Up to 300 in (7620 mm) Height: Up to 228 in (5791 mm)	250 sqr. ft (23 sqr. m)			
500, 530, 540, 560, 561, 562	2.5 in (64 mm), 3.25 in (83 mm)	STD 2.36 in (60 mm), HD 3 in (75 mm)	Width: Up to 300 in (7620 mm) Height: Up to 228 in (5791 mm)	250 sqr. ft (23 sqr. m)			
530, 560, 561	3.25 in (83 mm) with AnchorLoc	STD 2.36 in (60 mm), HD 3 in (75 mm)	Width: Up to 300 in (7620 mm) Height: Up to 228 in (5791 mm)	250 sqr. ft (23 sqr. m)			





www.pentagonshutters.com